


(51) International Patent Classification 5 :  A61F 13/15		A1	(11) International Publication Number: <b>WO 93/12747</b>
(21) International Application Number: PCT/US92/10610		(43) International Publication Date: 8 July 1993 (08.07.93)	
(22) International Filing Date: 9 December 1992 (09.12.92)			
(30) Priority data: 07/811,348 20 December 1991 (20.12.91) US			
(71) Applicant: THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US).			(74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45202 (US).
(72) Inventors: SNELLER, Diane, Lyn ; 3421 Banning Road, Cincinnati, OH 45239 (US). BRENNOCK, June, Turkannis ; 5790 Sovereign Drive, Cincinnati, OH 45241 (US). BERGMAN, Carl, Louis ; 6674 Quailrun Court, Loveland, OH 45140 (US).			(81) Designated States: AU, BB, BG, BR, CA, CS, FI, HU, JP, KP, KR, LK, MG, MN, MW, NO, NZ, PL, RO, RU, SD, UA, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG).
		Published <i>With international search report.</i>	

## (54) Title: ELASTICIZED SANITARY NAPKIN



## (57) Abstract

A unitary disposable absorbent article (20) such as a catamenial pad or incontinent pad is provided with an elasticized side flap (30) by operatively associating an elastic member (32) on both the upper surface and the lower surface of the side flap (30). The elastic member is preferably joined to the inner surface (48) of the side flap as well as the outer surface (46) of the side flap by folding it about the distal edge (50) of the side flap. In a preferred embodiment, the elastic member (32) comprises an elastomeric laminate of an elastomeric layer (42) and a coverstock layer (44), with the coverstock layer (44) being on the outside (46) of the product, so that the sanitary napkin is provided with soft longitudinal edges (38) which contact the wearer during use. In addition, the elastomeric laminate provides relatively low tension that while raising the side flaps (30) of the product to be a barrier against lateral leakage, also maintains the product in a shape which does not encourage fluid run-off or leakage at the ends of the pad as well as providing a bunching benefit.